



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet TAKTER® 4000



Safety Data Sheet dated 18/10/2017, version 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: TAKTER® 4000

Trade code: 14710/06

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Permanent adhesive (aerosol).

Uses advised against: Relevant uses are listed above. No other uses are recommended.

1.3. Details of the supplier of the safety data sheet

Company:

SILICONI COMMERCIALE SPA - Via Francia 4 Z.I. 36053 Gambellara (VI) ITALY Phone No.: +39 0444 649766

SILICONI COMMERCIALE SPA - ph n. +39 0444 649766 From Monday to Friday from 8 a.m. to 5 p.m.

Competent person responsible for the safety data sheet:

lab@siliconi.it

1.4. Emergency telephone number

SILICONI COMMERCIALE SPA - ph n. +39 0444 649766 From Monday to Friday from 8 a.m. to 5 p.m.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)



Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H222 Extremely flammable aerosol.

H229 Pressurized container: may burst if heated.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

The manufacturer cannot be held responsible in case of damages caused by incorrect use of the product.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

Aerosol containers may deform, explode and be thrown far away if exposed to temperature exceeding 50°C. Vapours forms flammable and explosive mixture with air; vapours are heavier than air, so they can accumulate in confined spaces and spread over the ground, causing fire risk even if the ignition occurs far away from the leakage.



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet

TAKTER® 4000

Aerosol contains an asphyxiating gas: avoid vapours accumulation in closed spaces because of asphyxiating risk due to the lack of oxygen. High vapour concentration, especially in closed and not proper ventilated spaces, may cause irritation of respiratory tract, nausea, drowsiness or dizziness.

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 30% - < 40%	dimethyl ether	Index number: 603-019-00-8 CAS: 115-10-6 EC: 204-065-8 REACH No.: 01-2119472128-37	2.2/1 Flam. Gas 1 H220 2.5 Press. Gas H280
>= 25% - < 30%	Methylal	CAS: 109-87-5 EC: 203-714-2 REACH No.: 01-2119664781-31	2.6/2 Flam. Liq. 2 H225
>= 7% - < 10%	Hydrocarbons, C6, isoalkanes, <5 % n-hexane	EC: 931-254-9 REACH No.: 01-2119484651-34	2.6/2 Flam. Liq. 2 H225 3.10/1 Asp. Tox. 1 H304 3.2/2 Skin Irrit. 2 H315 3.8/3 STOT SE 3 H336 4.1/C2 Aquatic Chronic 2 H411
>= 1.5% - < 2.5%	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-Hexane	EC: 926-605-8 REACH No.: 01-2119486291-36	2.6/2 Flam. Liq. 2 H225 3.10/1 Asp. Tox. 1 H304 3.8/3 STOT SE 3 H336 4.1/C2 Aquatic Chronic 2 H411 EUH066

For the wording of the listed hazard statements refer to section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothes and wash them before reuse.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath). In case of irritation seek medical advice.

In case of eye contact:

After contact with the eyes, rinse immediately with plenty of water with open eyelids for at least 15 minutes. Then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of ingestion:

Aerosol inadvertent ingestion is unlikely to happen. In case of ingestion, consult a doctor. Induce vomiting only in case the doctor suggest to do so. Don't give nothing orally if the person is unconscious.

In case of inhalation:

Move injured people to fresh air and keep them warm and at rest. Consult a doctor in case of difficult breathing.

Protective measurement for first-aiders:

See section 8.2 to check personal protective equipment for first-aid measures.

4.2. Most important symptoms and effects, both acute and delayed

For symptoms and effects due to the contained substances, see Section 11.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet

TAKTER® 4000

None in particular

SECTION 5: Firefighting measures

- 5.1. Extinguishing media
Suitable extinguishing media: CO₂ (carbon dioxide), dry chemical or chemical foam fire extinguisher.
Extinguishing media which must not be used for safety reasons: Do not use water jets on the burning product.
- 5.2. Special hazards arising from the substance or mixture
Do not inhale explosion and combustion gases. Combustion originates complex gas mixtures, containing carbon monoxide (CO), carbon dioxide (CO₂) and unburned hydrocarbons. Vapours are heavier than air, and may form flammable mixtures with air. Containers may deform and explode if exposed to temperature exceeding 50 °C.
- 5.3. Advice for firefighters
Wear full fire protection equipment (Type EN 11611 or EN469) with self-contained breathing apparatus (Type EN 137), visor helmet and neck protection (Type EN443), anti-heat gloves (Type EN407).
Collect contaminated fire extinguishing water separately. Fire extinguishing water must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.
Nebulised water can be used to cool down overheated containers after their exposure to fire. Prevent extinguishing media from entering the sewage or watercourses.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
Wear personal protection equipment (See Section 8). Indicate the danger of slipping clearly.
Remove all sources of ignition.
Remove persons to safety.
See protective measures under point 7 and 8.
- 6.2. Environmental precautions
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
- 6.3. Methods and material for containment and cleaning up
Provide proper ventilation. Use non-sparking tools and equipment. Wash with plenty of water. Contain spillage with non-combustible absorbing materials such as sand, earth, vermiculite, diatomaceous earth and dispose of the product by means of a waste disposal authorized company.
- 6.4. Reference to other sections
See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
Pressurized container. Do not perforate or burn even after use.
Do not use near flames or other possible sources of ignition. Do not smoke during work. Avoid accumulation of electrostatic charge. Do not spray on flames, warm surface or incandescent objects.
Use only in a well ventilated area. Vapours may burn, causing explosions. Prevent vapours accumulation by keeping doors and windows open and by assuring a proper ventilation.
Vapours are heavier than air, so they can accumulate in confined spaces and spread over the ground, causing fire risk even if the ignition occurs far away from the leakage.
Avoid direct exposure to sunlight.
Do not expose to temperatures exceeding 50°C/122°F.
Avoid skin and eye contact, vapours and mist inhalation.
Environmental protection measures: reduce the risk of releasing the mixture in the environment/air. Avoid inadvertent leakage, store far away from sewer.
Occupational hygiene measures: contaminated clothes have to be substituted before entering dining rooms. Do not eat, drink or smoke at workplace. Wash hands after using the mixture.
See section 8 for recommended protective devices.
- 7.2. Conditions for safe storage, including any incompatibilities
Technical measures and storage conditions: store in a well ventilated area, protect from direct sunlight.
Recommended storage temperature: between 15°C and 30°C.
Protect from flames, sparks, heat/combustion sources.
Keep containers in an upright and safe position, preventing them from falls and collisions. Do not store in corridors and stairs. Store only in original and tightly closes containers.
Do not perforate or open the containers. Keep far from food, beverages and animal feed.
Incompatible materials: do not store with comburents, self-flammable or self-heating substances, organic peroxides, oxidising agents, pyrophoric solids or liquids, explosives. See also section 10.



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet

TAKTER® 4000

Provisions for storage rooms: proper ventilation. Avoid electrostatic charge accumulation. Storage class: see section 15.1 (Seveso III).

7.3. Specific end use(s)
See section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

dimethyl ether - CAS: 115-10-6

EU - TWA(8h): 1920 mg/m³, 1000 ppm

Methylal - CAS: 109-87-5

ACGIH - TWA(8h): 1000 ppm - Notes: Eye irr, CNS impair

OEL 8h - 1000 mg/m³

Hydrocarbons, C6, isoalkanes, <5 % n-hexane

TLV TWA - 1200 mg/m³

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-Hexane

TLV TWA - 400 mg/m³ (115 ppm)

DNEL Exposure Limit Values

Methylal - CAS: 109-87-5

Worker Industry: 22 mg/kg - Consumer: 5.7 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects - Notes: bw/day

Worker Industry: 132 19141.03 - Consumer: 39 19141.03 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 9.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects - Notes: bw/day

Hydrocarbons, C6, isoalkanes, <5 % n-hexane

Consumer: 1301 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects - Notes: bw/day

Worker Industry: 13964 19141.03 - Consumer: 1377 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects - Notes: bw/day

Worker Industry: 5306 19141.03 - Consumer: 1137 19141.03 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects - Notes: bw/day

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-Hexane

Worker Industry: 13964 mg/kg - Consumer: 1377 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects - Notes: bw/day

Worker Industry: 5306 19141.03 - Consumer: 1131 19141.03 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 1301 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects - Notes: bw/day

PNEC Exposure Limit Values

Methylal - CAS: 109-87-5

Target: Marine water - Value: 1.4577 mg/l

Target: Fresh Water - Value: 14.577 mg/l

Target: Marine water sediments - Value: 1.3135 mg/kg

Target: Freshwater sediments - Value: 13.135 mg/kg

Target: Soil (agricultural) - Value: 4.6538 mg/kg

8.2. Exposure controls

Eye protection:

Wear goggles with lateral protection EN166 .

If exposure to vapours cause a sense of bother to eyes, use antigas mask with complete facial.

Protection for skin:

Wear clean antistatic and covering garments, and antistatic safety-shoes for professional use, S2 category (Type EN20345).

In case of long and frequent contact use protective garments, than are impervious to this product (Type EN340 – EN13034).

Protection for hands:

During manipulation is necessary protect hands with chemical resistant gloves Type EN374 (PVC, PE, neoprene, Nitrile, Viton, not natural Rubber). It is recommended to use gloves with Protective Index 6: permeation time >480min, Thickness >0,3mm. Change gloves in case of wear, cracks or internal contamination.

Respiratory protection:

Product concentration in air should be lower than exposure limit values. As the concentration exceed the threshold limit values, proper respiratory protection should be used. Use protective masks EN149 with FFP2 filters, half-face respirator type EN140 with EN143:A2 filters, or full face breathing mask EN136 with EN143:A2 filters.

Thermal Hazards:

The aerosol container if overheated, deforms, breaks and it can be thrown a considerable distance.

Environmental exposure controls:



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet

TAKTER® 4000

Avoid fog or aerosol formations. Do not eat or drink while using the product. Observe the general hygiene measures for the use of chemicals.

Appropriate engineering controls:

Adequately ventilate rooms where the product is stored and handled. Use only if the place is adequately ventilated.

Local ventilation might be necessary for certain operations. Minimize exposure concentration at the workplace. Use proper technical equipment to maintain the concentration below threshold limit values or guidelines for exposure.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:
Appearance and colour:	Pressurized container with liquefied gas	--
Odour:	Characteristic	--
Odour threshold:	N.A.	--
pH:	N.A.	--
Melting point / freezing point:	N.A.	--
Initial boiling point and boiling range:	N.A.	--
Flash point:	< 0 °C	--
Evaporation rate:	N.A.	--
Solid/gas flammability:	N.A.	--
Upper/lower flammability or explosive limits:	15 Vol % - 1.8 Vol %	--
Vapour pressure:	3-5 bar	--
Vapour density:	2	--
Relative density:	N.A.	--
Solubility in water:	insoluble	--
Solubility in oil:	soluble	--
Partition coefficient (n-octanol/water):	N.A.	--
Auto-ignition temperature:	> 300°C	--
Decomposition temperature:	N.A.	--
Viscosity:	N.A.	--
Explosive properties:	Non explosive	--
Oxidizing properties:	N.A.	--

9.2. Other information

Properties	Value	Method:
Miscibility:	N.A.	--
Fat Solubility:	N.A.	--
Conductivity:	N.A.	--
Substance Groups relevant properties	N.A.	--

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions. No hazardous reaction are expected under normal use conditions.

10.2. Chemical stability

Pressurized container. Do not perforate nor burn, even after use. Protect from direct sunlight. Do not expose to temperature exceeding 50°C/122°F. Refer to section 7 for information regarding handling and storage.

10.3. Possibility of hazardous reactions

No hazardous reaction are expected under normal use conditions. Vapours may form explosive mixtures with air. Aerosol containers may deform, explode and be thrown far away if exposed to temperature exceeding 50°C.

10.4. Conditions to avoid

Avoid exposure to sunlight. Avoid overheating and temperatures >50°C. Keep away from oxidizing agents.

10.5. Incompatible materials

Avoid contact with combustible agents. The product could catch fire. Avoid strong reducing and oxidising agents, strong acid and alkalis, warm object/materials.

10.6. Hazardous decomposition products

The product doesn't decompose under normal conditions. See section 5 for thermal decomposition.

SECTION 11: Toxicological information

11.1. Information on toxicological effects



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet

TAKTER® 4000

Toxicological information of the product:

TAKTER® 4000

- a) acute toxicity
Not classified
Based on available data, the classification criteria are not met
- b) skin corrosion/irritation
Not classified
Based on available data, the classification criteria are not met
- c) serious eye damage/irritation
Not classified
Based on available data, the classification criteria are not met
- d) respiratory or skin sensitisation
Not classified
Based on available data, the classification criteria are not met
- e) germ cell mutagenicity
Not classified
Based on available data, the classification criteria are not met
- f) carcinogenicity
Not classified
Based on available data, the classification criteria are not met
- g) reproductive toxicity
Not classified
Based on available data, the classification criteria are not met
- h) STOT-single exposure
Not classified
Based on available data, the classification criteria are not met
- i) STOT-repeated exposure
Not classified
Based on available data, the classification criteria are not met
- j) aspiration hazard
Not classified
Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

Methylal - CAS: 109-87-5

- a) acute toxicity:
Test: LC50 - Route: Inhalation - Species: Rat = 2000 mg/l - Notes: 6h/day
Test: LD50 - Route: Oral - Species: Rat = 6423 mg/kg
Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg
Hydrocarbons, C6, isoalkanes, <5 % n-hexane
- a) acute toxicity:
Test: LC50 - Route: Inhalation - Species: Rat > 20 mg/l - Duration: 4h
Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg
Test: LD50 - Route: Skin - Species: Rabbit > 3000 mg/kg
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-Hexane
- a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg
Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg
Test: LC50 - Route: Inhalation - Species: Rat > 20 mg/l

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

TAKTER® 4000

The product is classified: Aquatic Chronic 3 - H412

Methylal - CAS: 109-87-5

- a) Aquatic acute toxicity:
Endpoint: LC50 - Species: Fish > 1000 mg/l
Endpoint: EC50 - Species: Daphnia > 1200 mg/l - Duration h: 48

Hydrocarbons, C6, isoalkanes, <5 % n-hexane

- a) Aquatic acute toxicity:
Endpoint: LC50 - Species: Fish > 1 mg/l - Duration h: 48 - Notes: Oryzia latipes - Dati di materiali simili



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet

TAKTER® 4000

- Endpoint: LC50 - Species: Daphnia = 3.87 mg/l - Duration h: 48 - Notes: Daphnia Magna - Dati di materiali simili
Endpoint: SC2 - Species: Algae = 55 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata - Dati di materiali simili
Endpoint: NOEC - Species: Algae = 30 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata - Dati di materiali simili
- Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-Hexane
- a) Aquatic acute toxicity:
- Endpoint: LC50 - Species: Fish = 12 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss
Endpoint: EC50 - Species: Daphnia = 3 mg/l - Duration h: 48
Endpoint: EC50 - Species: Algae = 55 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata
- 12.2. Persistence and degradability
- None
- Hydrocarbons, C6, isoalkanes, <5 % n-hexane
- Biodegradability: Readily biodegradable - Test: N.A. - Duration: N.A. - %: N.A. - Notes: N.A.
- 12.3. Bioaccumulative potential
- N.A.
- 12.4. Mobility in soil
- N.A.
- 12.5. Results of PBT and vPvB assessment
- vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects
- None

SECTION 13: Disposal considerations

- 13.1. Waste treatment methods
- Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force. Containers may explode if exposed to temperature exceeding 50°C, even if they contain only product residual. Empty containers shouldn't be dispersed in the environment.
- European Waste Catalogue (EWC):
- Domestic uses: aerosol wastes originating from domestic use are not included in this regulation.
Industrial uses: aerosol waste is classified as 'Packaging containing residues of, or contaminated by, dangerous substances', EWC code 15.01.10.

SECTION 14: Transport information

- 14.1. UN number
- ADR-UN number: 1950
IATA-Un number: 1950
IMDG-Un number: 1950
- 14.2. UN proper shipping name
- ADR-Shipping Name: AEROSOLS, Flammable
IATA-Technical name: AEROSOLS, Flammable
IMDG-Technical name: AEROSOLS
- Limited Quantity: max 1000ml Total gross mass of package not exceed 30 kg LQ2
- 14.3. Transport hazard class(es)
- ADR-Class: 2, 5F
ADR-Label: Limited Quantity
IATA-Class: 2
IATA-Label: 2.1
IMDG-Class: 2
- 14.4. Packing group
- 14.5. Environmental hazards
- Marine pollutant: No
- 14.6. Special precautions for user
- IMDG-Technical name: AEROSOLS
- Limited Quantity: max 1000ml Total gross mass of package not exceed 30 kg LQ2
- IMDG-EMS: F-D
IMDG-MFAG: S-U
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code
- N.A.



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet

TAKTER® 4000

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) 2015/830

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

None

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P3a

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Full text of phrases referred to in Section 3:

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Hazard class and hazard category	Code	Description
Flam. Gas 1	2.2/1	Flammable gas, Category 1
Aerosols 1	2.3/1	Aerosol, Category 1
Press. Gas	2.5	Gases under pressure
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

Paragraphs modified from the previous revision:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

SECTION 2: Hazards identification

SECTION 3: Composition/information on ingredients

SECTION 4: First aid measures

SECTION 5: Firefighting measures

SECTION 6: Accidental release measures

SECTION 7: Handling and storage

SECTION 8: Exposure controls/personal protection

SECTION 9: Physical and chemical properties



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet

TAKTER® 4000

SECTION 10: Stability and reactivity
SECTION 11: Toxicological information
SECTION 12: Ecological information
SECTION 13: Disposal considerations
SECTION 14: Transport information
SECTION 15: Regulatory information
SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Aerosols 1, H222+H229	On basis of test data
Aquatic Chronic 3, H412	Calculation method

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information herein contained is based on our state of knowledge at the above-specified date. It refers solely to the indicated product and constitutes no guarantee of peculiar qualities.

It is responsibility of the user to make sure of the accuracy and the completeness of the information with respect to the specific intended use.

This MSDS cancels and replaces any previous release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
N.A.:	Not available
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.